

E-ACCŪSTAT® II

Electronic Thermostats



All of the E-ACCUSTAT® II controls feature electronic sensing and are housed in tamper-resistant locking cases.

They are available in single stage, multi stage, and heat pump models, with several optional features such as remote sensing, setback, and damper control.

Remote sensing models can use up to three remote sensors with averaging for optimum temperature control.

These controls are ideal for commercial applications such as warehouses and fast food restaurants or residential applications such as condominiums and other managed properties.

Please see specification sheet for detailed technical information.

Model #	Stages	Extra Features
LEMS2-AH11	1 CL/1 HT	
LEMS2-AH11-R	1 CL/1 HT	Remote sensing
LEMS2-AH11AS-RD	1 CL/1 HT	Remote sensing, setback, damper
LEMS2-AH22	2 CL/2 HT	
LEMS2-AH22-R	2 CL/2 HT	Remote sensing
LEMS2-AH22AS-RD	2 CL/2 HT	Remote sensing, setback, damper
Heat Pump		
LEHP2-AH12	1 CL/2 HT	
LEHP2-AH12AS-RD	1 CL/2 HT	Remote sensing, setback, damper
LEHP2-AH23	2 CL/3 HT	
LEHP2-AH23AS-RD	2 CL/3 HT	Remote sensing, setback, damper

Available Accessories

T24-7	Seven day timer	CP-013	Replacement locking pin
SRT-3	Remote sensor	CP-014	Replacement key
CP-012E	Replacement cover		